



Righton HD-5070B



Input	1 x D-SUB	VGA IN
	1 x BNC	HD/SD SDI Auto-switch
	3 x BNC	YPbPr
	1 x RCA	Analog Input
	1 x Mini-Din	S-Video
	1 x D-SUB(9 pin)	Tally Input
Output	1 x BNC	SDI Channel (Active Through Out)
Input Signal	Analog	Composite (CVBS) / S-Video 0.8Vpp
	SD-SDI	270Mbps, 525i (60/ 59.94) / 625i (50)
	HD-SDI	1080P/30Hz, 1080P/29.97Hz,
		1080P/25Hz,1080P/24Hz, 1080P/23.98Hz
		1080i/60Hz, 1080i/59.94Hz, 1080i/50Hz
		1035i/60Hz,1035i/59.94Hz
	720P/60Hz, 720P/59.94Hz, 720P/50Hz	
	VGA	640 X 350 (70/ 85)
		720 X 350 (70/ 85)
		640 X 400 (56/ 70/ 85)
720 X 400 (70/ 85)		
640 X 480 (60/ 66/ 72/ 75/ 85)		
800 X 600 (56/ 60/ 70/ 72 / 75/ 85)		
1024 X 768 (60/ 70/ 72/ 75/ 85)		



LCD	Size	7"
	Display Area	153 x 90 mm
	Resolution	1024 x 600 (16:9)
	Dot Pitch	0.297 mm
	Color	262K colors
	Luminance of White	250cd/m ²
	Contrast	400:1
	Response time	20 msec
	ViewingAngle (Typical)	H: 140 degrees ; V: 110 degrees
	Power	AC 100 - 240V (50 / 60Hz)
Power Consumption (Approx.)	20 Watts	
Operating Temperature	0 °C to 50 °C	
Storage Temperature	-10 °C to 60 °C	
Dimensions (W x H x D)	187 x 171 x 122 mm	
Accessory	Power supply /AC Power Cord	
Gross Weight	2 Kg + 200 g	